

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATERIAL NAME: Lonseal #650 Two-Component Solvent-Free Adhesive, Part A
MATERIAL USE: Sheet Vinyl Adhesive

MANUFACTURED FOR: Lonseal, Inc. **DATE PRINTED:** 7/31/2014
ADDRESS: 928 E. 238th Street **DATE REVISED:** 7/30/2014
Carson, CA 90745 **PREPARED BY:** E. Neihouse
(310) 830-7111

24 HOUR EMERGENCY PHONE NUMBERS: U.S. Transportation – CHEMTREC (800) 424-9300
INFOTRAC (800) 535-5053

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	%	CAS	OSHA PEL	ACGIH TLV
<i>Limestone</i>	30-60	1317-65-3	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	NL*
<i>Alkyl phenol blocked polyisocyanate</i>	10-30	Proprietary	NL*	NL*
<i>Epoxy resin</i>	7-13	25085-99-8	NL*	NL*
<i>Alkyl epoxy resin</i>	5-10	68609-97-2	NL*	NL*
<i>4-Nonylphenol, branched</i>	0.5-1.5	84852-15-3	NL*	NL*

	ORAL LD ₅₀ (RAT)	DERMAL LD ₅₀ (RABBIT)
<i>Alkyl epoxy resin (68609-97-2)</i>	17100 mg/kg	NL*
<i>4-Nonylphenol, branched (84852-15-3)</i>	580 mg/kg	2031 mg/kg

* - Not Listed

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard). This product is irritating to the eyes and skin. This product may cause sensitization by skin contact.

HAZARDOUS STATEMENT: CAUTION! IRRITANT. ALLERGEN. Irritating to eyes and skin. May cause sensitization by skin contact. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

POTENTIAL HEALTH EFFECTS

Eyes: This product is irritating to the eyes.

Ingestion: Acute ingestion may result in mild gastrointestinal distress.

Inhalation: This product may cause irritation to the respiratory system.

Skin: This product is irritating to the skin. Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization reaction.

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Hypersensitivity to product, allergies, and skin or respiratory disorders.

POTENTIAL ENVIRONMENTAL EFFECTS: None identified.

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

Ingestion: Flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

Inhalation: Immediately remove the affected person to fresh air. If symptoms persist, seek medical attention.

Skin: Flush with large amounts of water. If irritation persists, seek medical attention.

Notes to Physician: Provide general supportive measures and treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

FIRE HAZARD: Closed containers may rupture due to build-up of pressure when exposed to extreme heat.

FLASHPOINT AND METHOD: N/A

FLAMMABLE LIMITS (% BY VOLUME):

Upper: N/A

Lower: N/A

AUTOIGNITION TEMPERATURE: N/A

BURNING RATE: N/A

EXPLOSION DATA: None listed.

EXTINGUISHING MEDIA: Dry chemical (preferred,) foam, or water.

FIRE FIGHTING EQUIPMENT/PROCEDURES: Firefighters should wear full protective clothing including self contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide, and/or low molecular weight hydrocarbons.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear appropriate protective equipment and clothing during clean-up.

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

CONTAINMENT PROCEDURES: Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

ENVIRONMENTAL PRECAUTIONS: Dispose of waste material according to local, state, federal, and provincial environmental regulations.

CLEAN-UP PROCEDURES: Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up.

EVACUATION PROCEDURES: None identified.

SPECIAL PROCEDURES: Regulations vary. Consult local authorities before disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING PROCEDURES: Avoid getting this material into contact with your skin and eyes. Use this product with adequate ventilation. Wash hands after handling and before eating. Keep out of the reach of children.

STORAGE PROCEDURES: Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS:

Limestone (1317-65-3)

OSHA	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
NIOSH	10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)

ENGINEERING CONTROLS: Use general ventilation.

PERSON PROTECTIVE EQUIPMENT (PPE):

Eyes/Face: Wear safety glasses with side shields or goggles.

Respiratory: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Skin: The use of nitrile-latex gloves is recommended. Work clothing sufficient to prevent all skin contact should be worn, such as coveralls and long sleeves. Replace ripped or damaged gloves immediately. May cause sensitization by skin contact.

WORK HYGIENIC PRACTICES: Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Paste	Odor:	Slight Polyurethane odor
Physical State:	Paste	pH:	N/A
Vapor Pressure:	N/A	Vapor Density:	> 1
Boiling Point:	> 100.4 °F (38 °C)	Melting Point:	N/A
Solubility (H₂O):	Insoluble	Specific Gravity:	1.5
Evaporation Rate:	Slower than ether	VOC:	10 g/L (mixture)
Octanol/H₂O Coeff.:	N/A		

Physical Properties – Additional Information: The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity, or Certificate of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: This is a stable material.

Conditions to Avoid: Do not freeze.

INCOMPATIBILITY: This product may react with strong oxidizing agents.

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

HAZARDOUS DECOMPOSITION: Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE: See Section 3.

EFFECTS OF CHRONIC EXPOSURE: Not listed.

SENSITIZATION: This product may be sensitizing by prolonged skin contact.

CARCINOGENICITY: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

REPRODUCTIVE TOXICITY: Not listed.

TERATOGENICITY: Not listed.

EMBROTOXICITY: Not listed.

MUTAGENICITY: Not listed.

SYNERGISTIC MATERIAL: Not listed.

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:

COMPONENT ANALYSIS – AQUATIC TOXICITY

4-Nonylphenol, branched (84852-15-3)

Test & Species		Conditions
96 Hr LC50 Pimephales promelas	0.135 mg/L [flow-through]	
96 Hr LC50 Lepomis macrochirus	0.1351 mg/L [flow-through]	
96 Hr EC50 Pseudokirchneriella subcapitata	0.36 - 0.48 mg/L [static]	
72 Hr EC50 Psuedokirchneriella subcapitata	0.16 - 0.72 mg/L [static]	
72 Hr EC50 Desmodesmus subspicatus	1.3 mg/L	
48 Hr EC50 Daphnia magna	0.14 mg/L	

SECTION 13: DISPOSAL CONSIDERATIONS

COMPONENT WASTE NUMBERS: No EPA Waste Numbers are applicable for this product's components.

DISPOSAL INSTRUCTIONS: Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal. See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

SECTION 14: TRANSPORT INFORMATION

INTERNATIONAL TRANSPORTATION REGULATIONS: Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

General Product Information: All of the components of this product are listed on the U.S. EPA TSCA Inventory of Chemical Substances. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

Component Analysis: None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

STATE REGULATION

General Product Information: Other state regulations may apply. Check individual state requirements.

Component Analysis: The following components appear on one or more of the following state hazardous substances list:

Limestone (1317-65-3): MA, MN, NJ, PA, RI

CALIFORNIA PROPOSITION 65: This product contains a chemical known to the state of California to cause cancer.

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

CANADA WHMIS INFORMATION

General Product Information:



Component Analysis – WHMIS IDL: No components are listed in the WHMIS IDL.

ADDITIONAL REGULATORY INFORMATION

General Product Information: Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

Component Analysis – Inventory

Component	CAS #	TSCA	CAN	EEC
Limestone	1317-65-3	Yes	NDSL	EINECS
Epoxy resin	25085-99-8	Yes	DSL	No
Alkyl epoxy resin	68609-97-2	Yes	DSL	EINECS
4-Nonylphenol, branched	84852-15-3	Yes	DSL	EINECS

SECTION 16: OTHER INFORMATION

HMIS RATINGS:

Health: 2
Flammability: 0
Physical Hazard: 0
Personal Protection: Safety glasses, gloves
Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3= Serious; 4 = Severe

NFPA CODES:

Health: 2
Flammability: 0
Instability/Reactivity: 0
Special: None
NFPA Ratings: 0 = Minimal; 1 = Slight; 2 = Moderate; 3= Serious; 4 = Severe

GENERAL STATEMENTS:

Keep out of the reach of children.
For professional or industrial use only.
If you cannot read, or do not understand all directions, cautions, and warnings, do not use this product.

DISCLAIMER: Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. This information relates only to the product designated herein, and does not relate to its use in combination with other material or in any other process. The manufacturer makes no representations and assumes no liability for any direct, incidental, or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State, or provincial and local laws. Conditions of use are beyond our control and therefore

MATERIAL SAFETY DATA SHEET

Lonseal #650 Two-Component Solvent-Free Adhesive, Part A

users are responsible to verify this data under their own conditions to determine suitability for their purpose.