


MIRO CUBE 2 SPECIFICATION ORDER CODES

Use these codes to specify your fixture type.



- MIRO** : Miro Cube 2
- W** : WNC (2700-6000K)
4 : 4C (RGBW)
A : 4CA (RGBA)
U : UV365
T : Color Tuned*
0 : White Tuned*
- B** : Black
W : White
C : Custom Color*
- R** : RJ45
C : Classic Conversion**
 (5-pin XLR, Powercon, LCD Display UI)

EXAMPLE:
 Miro Cube 2 WNC fixture in black finish with RJ45 data interface:
 MIRO-W-B-R

*If any of these options are selected, please complete the Custom Modifications section below.
 ** Classic Conversion is only available in a black finish. Custom Modifications are not available for Classic Conversion.

MIRO CUBE 2 ACCESSORY SPECIFICATION ORDER CODES

Use these codes to specify any accessories you want your fixture to have.



- MIROA** : Miro Cube 2 Accessory
- X** : Standard Yoke*
Y : Data Track Adapter*
Z : Other Track Adapter (Halo, Global, etc.)**
- O** : Miro Cube 2 OPTI-SCULPT™ Lens Kit (included with fixture)
C : Specified OPTI-SCULPT™ Lens***
X : N/A
- B-B** : Barn Door Black
B-W : Barn Door White
Y-B : Top Hat Black
Y-W : Top Hat White
E-B : Egg Crate Black
X : N/A
- M** : myMIX[®] CONNECT RJ45
X : N/A

EXAMPLE:
 Miro Cube 2 4C fixture in white finish with RJ45 data interface, standard yoke, the included OPTI-SCULPT Lens Kit, white barn doors, and myMIX Connect:
 MIRO-4-W-R
 MIROA-X-O-B-W-M

*Yoke and Track Adapters will match the black or white housing finish chosen for the fixture.
 ** Not available for all styles of track. Minimum order quantity required.
 *** If this option is selected, please complete the Custom Modifications section below.

MIRO CUBE 2 CUSTOM MODIFICATION SPECIFICATION ORDER CODES

Only use these codes if you need to provide details about the fixture's custom color/color temperature preset, or the custom finish for the fixture housing.



- MIROC** : Custom Modification Required
- TH(XXX)S(YY)** : X=Hue, Y=Saturation
0(####) : #=Color Temperature K
- FRAL(####)** : RAL Color Number
- OSXXXX** : OPTI-SCULPT Lens Number

EXAMPLE:
 Miro Cube 2, preset to a bright blue color, in a bright blue housing, with RJ45 data interface, standard yoke, 10°x60° OPTI-SCULPT Lens, and no other accessories.
 MIRO-T-C-R
 MIROA-X-C-X-X
 MIROC-TH(233)S(92)-FRAL(5002)-OS1060

Name: _____ Date: _____

Company Name: _____

Project: _____